

CL10 SPECIFICATIONS

OVERALL DIMENSIONS

WIDTH = 43" DEPTH = 45-1/2"
HEIGHT = 78-1/2" (81" GAS) HEIGHT WITH DOOR OPEN = 103"
DOOR OPENING = 28-3/4" WIDE x 30" HIGH

HOT WATER SYSTEM

1/2" HOT WATER SUPPLY REQUIRED, UNION PROVIDED
140° F. WATER REQUIRED AT THE MACHINE
78 GPH AT 20 PSI (6-1/2 GAL./CYCLE x 12 CYCLES/HR.)
RINSE BOOSTER: ONE 9 kW HEATING ELEMENT IN A 8-1/2 GAL. RINSE TANK

FULL LOAD AMPS

| | 208 VOLT | 230 VOLT | 460 VOLT |
|-----------------------|----------|----------|----------|
| ELECTRIC | 71.0 | 65.2 | 33.6 |
| GAS/STEAM (INJECTED) | 46.0 | 42.6 | 22.3 |
| STEAM (RECIRCULATING) | 22.0 | 20.0 | 11.0 |

GAS SYSTEM (GAS MACHINES ONLY)

1/2" GAS SUPPLY
NATURAL: 6" W.C. MINIMUM INLET, 3-1/2" W.C. MAIN MANIFOLD = 36,000 BTU
PROPANE: 11" W.C. MINIMUM INLET, 6" W.C. MAIN MANIFOLD = 36,000 BTU
3" STAINLESS STEEL CHIMNEY ON BACK OF MACHINE

STEAM SYSTEM (STEAM MODELS ONLY)

3/4" STEAM LINE, 1015 PSI – 15 LBS. PER HOUR AVERAGE - INJECTED
33 LBS. PER HOUR AVERAGE - RECIRCULATING

WASH SYSTEM

7-1/2 HP PUMP RECIRCULATES APPROXIMATELY 130 GPM @ 55 PSI

HEAT: >ELECTRIC – ONE 9 kW HEATING ELEMENT
>GAS – TWO 18,000 BTU RATED INFRARED BURNERS = 36,000 BTU
>STEAM – DIRECT INJECTION, 10-15 PSI, 15 LBS. PER HOUR AVERAGE
RECIRCULATED, 10-15 PSI, 33 LBS. PER HOUR AVERAGE

25 GALLON WASH TANK
1-1/2" COPPER DRAIN
8" STEAM EXHAUST VENT COMPANION FLANGE