

EC10 SPECIFICATIONS

OVERALL DIMENSIONS

WIDTH = 32" DEPTH = 37-1/4"
HEIGHT = 78" HEIGHT WITH DOOR OPEN = 103"
DOOR OPENING = 28-3/4" WIDE x 30" HIGH

HOT WATER SYSTEM

1/2" HOT WATER SUPPLY REQUIRED, UNION PROVIDED
140° F. WATER REQUIRED AT THE MACHINE
30 GPH AT 20 PSI (2-1/2 GAL./CYCLE x 12 CYCLES/HR.)
RINSE BOOSTER: ONE 4.5 kW HEATING ELEMENT IN A 5 GAL. RINSE TANK

FULL LOAD AMPS

	208 VOLT	230 VOLT	460 VOLT
ELECTRIC	53.5	47.9	25.0
STEAM (Injected or Recirculating)	16.0	14.0	8.0

STEAM SYSTEM (STEAM MODELS ONLY)

3/4" STEAM LINE, 10-15 PSI – 25 LBS. PER HOUR AVERAGE - RECIRCULATING

WASH SYSTEM

5 HP PUMP RECIRCULATES APPROXIMATELY 80 GPM @ 45 PSI

HEAT: >ELECTRIC – ONE 9 kW HEATING ELEMENT
>STEAM – INJECTED OR RECIRCULATING, 10-15 PSI, 25 LBS. PER HOUR AVERAGE

25 GALLON WASH TANK
1-1/2" COPPER DRAIN
6" STEAM EXHAUST VENT COMPANION FLANGE
(REQUIRES PVC, CPVC, OR STAINLESS STEEL FIELD INSTALLED DUCT)