

## RW1548 SPECIFICATIONS

### OVERALL DIMENSIONS

WIDTH = 57" (60" WITH SIDE SUPPORT ANGLES)  
DEPTH = 65"  
HEIGHT (OVERALL) = 92-1/2" (94-1/2" GAS)  
HEIGHT (PIT MODEL) = 81-1/2" ABOVE FLOOR

### HOT WATER SYSTEM

1" HOT WATER SUPPLY REQUIRED, UNION PROVIDED  
140° F. WATER REQUIRED AT THE MACHINE  
168 GPH AT 20 PSI (14 GAL./CYCLE x 12 CYCLES/HR.)  
RINSE BOOSTER: TWO 9kW HEATING ELEMENTS IN A 20 GAL. RINSE TANK

### FULL LOAD AMPS

	208 VOLT	230 VOLT	460 VOLT
ELECTRIC	133.1	122.3	62.1
GAS/STEAM (INJECTED)	95.6	88.4	45.2
STEAM (RECIRCULATING)	45.6	43.2	22.6

### GAS SYSTEM (GAS MACHINES ONLY)

1/2" GAS SUPPLY CONNECTION  
NATURAL: 7" W.C. MINIMUM INLET, 6" W.C. MAIN MANIFOLD = 66,000 BTU  
PROPANE: 11" W.C. MINIMUM INLET, 10" W.C. MAIN MANIFOLD = 66,000 BTU  
4" STAINLESS STEEL CHIMNEY

### STEAM SYSTEM (STEAM MODELS ONLY)

3/4" STEAM LINE, 10-15 PSI - 37 LBS. / HR. AVERAGE – INJECTED  
76 LBS. / HR. AVERAGE – RECIRCULATING

### WASH SYSTEM

10 HP & 5 HP PUMPS IN SERIES RECIRCULATE APPROXIMATELY 240 GPM @ 60 PSI.

HEAT: >ELECTRIC – ONE 9 kW AND ONE 4.5 kW HEATING ELEMENT  
>GAS – THREE 22,000 BTU RATED INFRARED BURNERS = 66,000 BTU  
>STEAM – DIRECT INJECTION, 10-15 PSI, 37 LBS / HR AVERAGE  
RECIRCULATED, 10-15 PSI, 76 LBS / HR AVERAGE

65 GALLON WASH TANK  
1-1/2" COPPER DRAIN  
8" STEAM EXHAUST VENT COMPANION FLANGE