

RW2580 SPECIFICATIONS

OVERALL DIMENSIONS

WIDTH = 55" (57" WITH SUPPORT ANGLES)
DEPTH = 96"
HEIGHT = 81" FROM FLOOR WITH MACHINE IN A PIT (17" BELOW FLOOR)
DOOR OPENING = 31" WIDE x 77" HIGH

HOT WATER SYSTEM

1-1/4" HOT WATER SUPPLY REQUIRED, UNION PROVIDED
140° F. WATER REQUIRED AT THE MACHINE
260 GPH AT 20 PSI (26 GAL./CYCLE x 10 CYCLES/HR.
RINSE BOOSTER: THREE 9kW HEATING ELEMENTS IN A 30 GAL. RINSE TANK

FULL LOAD AMPS

	208 VOLT	230 VOLT	460 VOLT
ELECTRIC	219.3	196.4	99.2
GAS	145.5	129.8	66.3
STEAM	69.3	60.8	31.4

GAS SYSTEM (GAS MACHINES ONLY)

3/4" SUPPLY - CONSULT FACTORY FOR CURRENT OPTIONS

STEAM SYSTEM (STEAM MODELS ONLY)

1-1/2" STEAM LINE, 10-15 PSI - 125 LBS. / HR. AVERAGE
INJECTED OR RECIRCULATING WASH, RECIRCULATING RINSE

WASH SYSTEM

25 HP PUMP RECIRCULATES APPROXIMATELY 480 GPM @ 55 PSI.

HEAT: >ELECTRIC – THREE 9kW HEATING ELEMENTS
>STEAM – DIRECT INJECTION, 10-15 PSI
RECIRCULATING, 10-15 PSI

160 GALLON WASH TANK
2" NPT DRAIN CONNECTION
12" STEAM EXHAUST VENT COMPANION FLANGE